

Architape Tuneable 100/50

V. Architape Tuneable 100/50/.01

APPLICATION

- General LED Lighting
- Cove LED Lighting
- Linear LED lighting
- Backlighting
- Signage and Advertising
- Furniture Lighting & More

PRODUCT FEATURES

- Tunable white 2000K-6500K wide color range
- Single Bin (1/16th) LEDs or 3 STEP MacAdam
- 112 LEDs per
- High CRI Ra80+ or Ra90+
- 10 mm width
- Reverse voltage protection
- 120° beam angle
- Highest quality components, Japanese NICHIA LED chips
- IC stabilized current design
- Efficacy up to 165 lm/W
- Thick copper PCB
- Dimmable
- 24V DC voltage input
- Thermal conductive adhesive tape on backside for better heat conduction
- Can be cut in 125 mm length segments



TECHNICAL DETAILS

PRODUCT NO.	LED QUANTITY	WATTAGE	LED BRAND	COLOR	CRI	LUMIN/M	EFFICACY	MAX.	CUTTING
ARCHITAPE TUNEABLE 100/50/820/865	56 LEDs/m(56+56)	48 W/M	Nichia	2000-6500K	80+	5670 lm/m	118 Lm/W	2 M	125mm
ARCHITAPE TUNEABLE 100/50/825/857	56 LEDs/m(56+56)	48 W/M	Nichia	2500-5700K	80+	6126 lm/m	128 Lm/W	2 M	125mm
ARCHITAPE TUNEABLE 100/50/827/857	56 LEDs/m(56+56)	48 W/M	Nichia	2700-5700K	80+	6602 lm/m	137 Lm/W	2 M	125mm
ARCHITAPE TUNEABLE 100/50/827/850	56 LEDs/m(56+56)	48 W/M	Nichia	2700-5000K	80+	6766 lm/m	141 Lm/W	2 M	125mm
ARCHITAPE TUNEABLE 100/50/920/965	56 LEDs/m(56+56)	48 W/M	Nichia	2700-5000K	90+	4821 lm/m	100 Lm/W	2 M	125mm
ARCHITAPE TUNEABLE 100/50/925/957	56 LEDs/m(56+56)	48 W/M	Nichia	2700-5000K	90+	5164 lm/m	108 Lm/W	2 M	125mm
ARCHITAPE TUNEABLE 100/50/927/950	56 LEDs/m(56+56)	48 W/M	Nichia	2700-5000K	90+	5647 lm/m	118 Lm/W	2 M	125mm