

## ARCHITAPE PRO 50-15 FLEXIBLE LED STRIP


V.ARCHITAPEPRO5015.01

### APPLICATION

- General LED Lighting
- Cove LED Lighting
- Linear LED lighting
- Backlighting
- Signage and Advertising
- Furniture Lighting & More

### PRODUCT FEATURES

- Japanese NICHIA LED Chips
- Single Bin (1/16<sup>th</sup>) LED or 3 Step MacAdam
- Stabilized Current Design
- Efficiency up to 156
- Thick Copper PCB
- 56 LEDs Per Metre
- High CRI80+, CRI90+ or CRI98+
- 7.5mm Width
- 24V DC Input
- Reverse Voltage Protection
- Thermal Conductive Adhesive Taa
- 120° Beam Angle
- 125mm Cut Points
- Dimmable



## TECHNICAL DETAILS

	LED QUANTITY	WATTAGE	LED BRAND	COLOR	CRI	LUMIN/M	EFFICACY	MAX.	CUTTING
<b>ARCHITAPE PRO 50/15/820</b>	56 LED/M	14.2 W/M	Nichia 757	2000K	80+	1434 lm/m	101 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/822</b>	56 LED/M	14.2 W/M	Nichia 757	2200K	80+	1550 lm/m	109 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/825</b>	56 LED/M	14.2 W/M	Nichia 757	2500K	80+	1720 lm/m	121 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/827</b>	56 LED/M	14.2 W/M	Nichia 757	2700K	80+	2019 lm/m	142 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/830</b>	56 LED/M	14.2 W/M	Nichia 757	3000K	80+	2080 lm/m	146 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/835</b>	56 LED/M	14.2 W/M	Nichia 757	3500K	80+	2093 lm/m	147 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/840</b>	56 LED/M	14.2 W/M	Nichia 757	4000K	80+	2093 lm/m	147 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/850</b>	56 LED/M	14.2 W/M	Nichia 757	5000K	80+	2243 lm/m	158 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/857</b>	56 LED/M	14.2 W/M	Nichia 757	5700K	80+	2140 lm/m	141 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/865</b>	56 LED/M	14.2 W/M	Nichia 757	6500K	80+	2140 lm/m	151 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/920</b>	56 LED/M	14.2 W/M	Nichia 757	2000K	90+	1191 lm/m	84 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/922</b>	56 LED/M	14.2 W/M	Nichia 757	2200K	90+	1289 lm/m	91 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/925</b>	56 LED/M	14.2 W/M	Nichia 757	2500K	90+	1398 lm/m	98 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/927</b>	56 LED/M	14.2 W/M	Nichia 757	2700K	90+	1681 lm/m	118 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/930</b>	56 LED/M	14.2 W/M	Nichia 757	3000K	90+	1724 lm/m	121 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/935</b>	56 LED/M	14.2 W/M	Nichia 757	3500K	90+	1766 lm/m	124 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/940</b>	56 LED/M	14.2 W/M	Nichia 757	4000K	90+	1785 lm/m	126 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/950</b>	56 LED/M	14.2 W/M	Nichia 757	5000K	90+	1890 lm/m	133 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/957</b>	56 LED/M	14.2 W/M	Nichia 757	5700K	90+	1878 lm/m	132 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/965</b>	56 LED/M	14.2 W/M	Nichia 757	6500K	90+	1866 lm/m	131 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/027</b>	56 LED/M	14.2 W/M	Nichia 757	2700K	98+	1382 lm/m	97 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/030</b>	56 LED/M	14.2 W/M	Nichia 757	3000K	98+	1412 lm/m	99 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/035</b>	56 LED/M	14.2 W/M	Nichia 757	3500K	98+	1443 lm/m	102 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/040</b>	56 LED/M	14.2 W/M	Nichia 757	4000K	98+	1461 lm/m	103 Lm/W	4 M	125 mm
<b>ARCHITAPE PRO 50/15/050</b>	56 LED/M	14.2 W/M	Nichia 757	5000K	98+	1584 lm/m	112 Lm/W	4 M	125 mm