

ARCHITAPE PRO 50-25 FLEXIBLE LED STRIP


V.ARCHITAPEPRO5025.01

APPLICATION

- General LED Lighting
- Cove LED Lighting
- Linear LED lighting
- Backlighting
- Signage and Advertising
- Furniture Lighting & More

PRODUCT FEATURES

- Japanese NICHIA LED Chips
- Single Bin (1/16th) LED or 3 Step MacAdam
- Stabilized Current Design
- Efficiency up to 149
- Thick Copper PCB
- 56 LEDs Per Metre
- High CRI80+, CRI90+ or CRI98+
- 7.5mm Width
- 24V DC Input
- Reverse Voltage Protection
- Thermal Conductive Adhesive Taa
- 120° Beam Angle
- 125mm Cut Points
- Dimmable



TECHNICAL DETAILS

	LED QUANTITY	WATTAGE	LED BRAND	COLOR	CRI	LUMIN/M	EFFICACY	MAX.	CUTTING
ARCHITAPE PRO 50/25/820	56 LED/M	24 W/M	Nichia 757	2000K	80+	2296 lm/m	96 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/822	56 LED/M	24 W/M	Nichia 757	2200K	80+	2482 lm/m	103 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/825	56 LED/M	24 W/M	Nichia 757	2500K	80+	2756 lm/m	115 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/827	56 LED/M	24 W/M	Nichia 757	2700K	80+	3235 lm/m	135 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/830	56 LED/M	24 W/M	Nichia 757	3000K	80+	3332 lm/m	138 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/835	56 LED/M	24 W/M	Nichia 757	3500K	80+	3352 lm/m	140 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/840	56 LED/M	24 W/M	Nichia 757	4000K	80+	3352 lm/m	140 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/850	56 LED/M	24 W/M	Nichia 757	5000K	80+	3582 lm/m	149 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/857	56 LED/M	24 W/M	Nichia 757	5700K	80+	3417 lm/m	142 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/865	56 LED/M	24 W/M	Nichia 757	6500K	80+	3417 lm/m	142 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/920	56 LED/M	24 W/M	Nichia 757	2000K	90+	1881 lm/m	78 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/922	56 LED/M	24 W/M	Nichia 757	2200K	90+	2035 lm/m	85 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/925	56 LED/M	24 W/M	Nichia 757	2500K	90+	2208 lm/m	92 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/927	56 LED/M	24 W/M	Nichia 757	2700K	90+	2675 lm/m	111 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/930	56 LED/M	24 W/M	Nichia 757	3000K	90+	2743 lm/m	114 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/935	56 LED/M	24 W/M	Nichia 757	3500K	90+	2811 lm/m	117 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/940	56 LED/M	24 W/M	Nichia 757	4000K	90+	2840 lm/m	118 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/950	56 LED/M	24 W/M	Nichia 757	5000K	90+	3015 lm/m	126 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/957	56 LED/M	24 W/M	Nichia 757	5700K	90+	2995 lm/m	125 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/965	56 LED/M	24 W/M	Nichia 757	6500K	90+	2976 lm/m	124 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/027	56 LED/M	24 W/M	Nichia 757	2700K	98+	2187 lm/m	91 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/030	56 LED/M	24 W/M	Nichia 757	3000K	98+	2235 lm/m	93 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/035	56 LED/M	24 W/M	Nichia 757	3500K	98+	2283 lm/m	95 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/040	56 LED/M	24 W/M	Nichia 757	4000K	98+	2312 lm/m	96 Lm/W	3 M	125 mm
ARCHITAPE PRO 50/25/050	56 LED/M	24 W/M	Nichia 757	5000K	98+	2519 lm/m	105 Lm/W	3 M	125 mm