

	<ul style="list-style-type: none"> <li>• Product installation must be carried out by a qualified professional.</li> <li>• Before installing, make sure that electrical power is turned <b>OFF</b>.</li> <li>• LED tapes must be installed in accordance with all applicable regulations &amp; standards.</li> <li>• LED tapes and components should not be subjected to any form of mechanical stress.</li> <li>• Do not operate if the luminaire has been damaged.</li> <li>• Installation/handling/sealing operating ambient temperature is +18°C to +35°C.</li> <li>• During installation, use gloves to protect the surface from dirt and fingerprints.</li> <li>• Product warranty does not cover damage due to faulty installation and/or misuse.</li> <li>• For further information, please contact Architape.</li> </ul>
--	--

**DIMENSIONS**

<p><b>LED strip</b></p>	<p><b>Polycarbonate mounting profile</b></p>	<p><b>Screws</b></p>
-------------------------	--	----------------------

Max. bend radius 10 cm (3.94 in)

LED strips may only be turned on when rolled out.  
Keep the LED strip on the reel while applying it onto the mounting profile.

Aqua can be cut with a pair of scissors at the designated cutting point between the steps.

2 mm (0.07 in)

To account for possible expansion/contraction due to temperature changes, leave a 2 mm (0.07 in) gap between the mounting profiles.

**PROFILE MOUNTING**

**1**

**2**

